



TRBOnet *Watch* v 2.5

January 2017

The Neocom team is delighted to announce the availability of the new version of TRBOnet Watch

Highlighted features

Support for new systems and modes

- + **Capacity Max.** On a Capacity Max system with Data Gateway, you are now able to monitor the following types of traffic: Location, Telemetry, Text and Voice.
- + **Extended Range Direct Mode for Single Repeater systems**
- + **Digital Voting for IP Site Connect, Capacity Plus (Single Site) and Linked Capacity Plus (Capacity Plus Multi Site)**

New diagrams

- + **Activities by Radio.** The diagram shows the top 5 busiest radios by the amount or duration of calls and data sessions.
- + **All Channels Busy.** The improved version of the chart allows you to set a threshold. The system is considered busy if the number of busy channels exceeds a predefined value.

Other features and improvements

- + **Connect Plus** can now be shown in Live Monitor as a whole system or on a site level for better viewing.
- + **Extended Diagnostics** displays RDAC values received from all your repeaters; includes RSSI, AC Voltage, Output Power, and VSWR for SLR repeaters.
- + **Live Monitor** displays the number of ongoing voice calls and data sessions in your network.
- + **Optimized RDAC traffic** between the Watch server and the radio network.

For the full list and details of new features, improvements and fixes please see the **Release Notes**.